

重荷载脚轮

TP6600 系列

FEATURES

特征

顶板: 6.0t钢板
 支架: 6.0t钢板
 转环: 上 5/16" & 下 1/4" 钢珠
 旋转中心大小: M14 螺栓和螺母

用处

多种重载物品搬运车
 汽车工业用托盘



SERIES



WHEEL OPTION

PRO	MIR	RCI	PCI
			
尺寸 4" (102mm) 5" (127mm) 6" (152mm) 8" (203mm)	尺寸 4" (102mm) 5" (127mm) 6" (152mm) 8" (203mm)	尺寸 4" (102mm) 5" (127mm) 6" (152mm) 8" (203mm)	尺寸 4" (102mm) 5" (127mm) 6" (152mm) 8" (203mm)

MODEL DESCRIPTIONS

方向	定向	轮径(mm)	轮宽(mm)	轮子种类	轴承	承重Kg	安装高度	转转半径
TP6640-**-RCI TG PCI TG PRO MIR B/BTG	TP6640R-RCI TG PCI TG PRO MIR B/BTG	4(102)	2(50)	橡胶/铁	滚轴(#003)	160	143	90
				聚氨酯/铁		320		
				聚氨酯/塑料		150		
				橡胶/塑料	滚珠(#6003)	130		
TP6650-**-RCI TG PCI TG PRO TG MIR B/BTG	TP6650R-RCI TG PCI TG PRO TG MIR B/BTG	5(127)	2(50)	橡胶/铁	滚轴(#003)	170	165	108
				聚氨酯/铁		360		
				聚氨酯/塑料		180		
				橡胶/塑料	滚珠(#6003)	150		
TP6660-**-RCI TG PCI TG PRO TG MIR B/BTG	TP6660R-RCI TG PCI TG PRO TG MIR B/BTG	6(152)	2(50)	橡胶/铁	滚轴(#003)	185	187	114
				聚氨酯/铁		360		
				聚氨酯/塑料		210		
				橡胶/塑料	滚珠(#6003)	180		
TP6680-**-RCI TG PCI TG PRO TG MIR B/BTG	TP6680R-RCI TG PCI TG PRO TG MIR B/BTG	8(203)	2(50)	橡胶/铁	滚轴(#003)	225	241	165
				聚氨酯/铁		400		
				聚氨酯/塑料		220		
				橡胶/塑料	250			

STEM OPTION

序号	类型	规格 (m/m)
01	长方形	整体尺寸 114 x 102
		孔距 92 x 67 to 76 x 76
		安装孔尺寸 M10 (3/8")
04	长方形	整体尺寸 140 x 127
		孔距 114 x 105
		安装孔尺寸 M10 (3/8")
21	丝杆形	3/4" x 10 1/2 x 50mm

OPTION

<p>TLB</p>  <p>边刹</p>	<p>DW</p>  <p>双面焊接</p>	<p>PSL-4</p>  <p>正刹</p>
--	---	--