

特殊设备用脚轮

TP8403 系列

FEATURES

特征

顶板: 3.0t 钢珠
支架: 2.6t 钢珠
转环: #6203ZZ-2RS 精密滚珠轴承
旋转中心大小: $\varnothing 15.0$
轴: 5/16" (M8) 螺栓和螺母

用处

医疗器械
电子设备



SERIES

WHEEL OPTION

MIR	TSR
	
尺寸 4" (102mm) 5" (127mm)	尺寸 4" (102mm) 5" (127mm)



MODEL DESCRIPTIONS

 万向	 轮径(mm)	 轮宽(mm)	 轮子种类	 轴承	 承重Kg	 安装高度	 旋转半径
	TP8433-* *-MIR TG	3 (76)	1 1/4 (32)	橡胶 / 塑料	滚珠 (#608)	50	118
TP8443-* *-MIR TG	4 (102)	橡胶 / 塑料		70		145	92
TP8453-* *-MIR TG TSR TG	5 (127)	TSR / 塑料		90		171	103

STEM OPTION

序号	类型	规格(m/m)			
01	长方形	整体尺寸	92 x 64		
		孔距	75 x 45		
		安装孔尺寸	M8 (5/16")		
02		整体尺寸	94 x 64		
		孔距	75 x 45 to 80 x 50		
		安装孔尺寸	M8 (5/16")		
07	整体尺寸	70 x 95			
	孔距	70 x 52 to 74 x 45			
	安装孔尺寸	M8 (5/16")			
23	丝杆形	5/8" x 11 x 25mm	安装高度(m/m)		
			3"(76)	4"(102)	5"(127)
25		M12 x 1.75P x 25mm	118	145	171

OPTION

SWB	DUL
	
全刹	